

### Section 1 – Identification of Chemical Product and Company

Code	Description	Size	Colour
12104	Accent Plumbing Silicone	280 ml	Clear

Recommended use:	Sealant
Supplier contact details:	Soudal Ltd
	14 Avalon Drive
	Nawton
	Hamilton 3200
	New Zealand
	Freephone: 0800 70 10 80
	Phone: (07) 847 5540
	Fax: (07) 847 0324
	Email: <a href="mailto:info@soudal.co.nz">info@soudal.co.nz</a>
	Website: <a href="http://www.soudal.co.nz">www.soudal.co.nz</a>
POISON CENTRE NUMBER: 0800 764 766 (24 hours)	

### Section 2 – Hazard Identification

#### Statement of Hazardous Nature

This product is classified as:

**HAZARDOUS SUBSTANCE** according to the criteria of HSNO.

**NOT REGULATED** under NZS5433:2007 Transport of Dangerous Goods on Land

#### Hazardous Substances and New Organisms (HSNO) classification:

Classification	Hazard statements
<b>Eye Effects Category 2</b> <b>6.4A</b>	H319 Causes serious eye irritation
<b>Skin Sensitisation Category 1</b> <b>6.5B</b>	H317 May cause an allergic skin reaction
<b>Invertebrate Hazard Category 1</b> <b>9.4A</b>	H441 Very toxic to terrestrial invertebrates

HSNO Signal Word :

**WARNING**



#### Precautionary Statements:

Ensure all safety directions are read and understood before handling  
Keep out of reach of children.

Avoid breathing fumes/ sprays/ mists/ vapours  
Use only outdoors or in a well ventilated area  
Wear protective clothing/ gloves and eye/ face protection

Wash thoroughly after handling.  
Do not eat, drink or smoke while handling  
Avoid release to the environment

### Section 3 - Composition/Information on Ingredients

Ingredient	CAS No.	Individual HSNO classification	Concentration (% by Wt.)
Siloxanes and Silicones, di-Me, hydroxy terminated	70131-67-8	Eye Effects Category 2; Invertebrate Hazard Category 1	40 – 50
Methyltri(methylethylketoxime)silane	22984-54-9	Flammable Liquid Category 3; Acute Oral Toxicity Category 5; Acute Dermal Toxicity	1 – 10

		Category 5; Skin Sensitiser Category 1; STOT – SE NE Category 3;	
N-[3-(trimethoxysilyl)propyl]ethylene diamine	1760-24-3	Chronic Aquatic Hazard Category 3	< 1
Dioctylin dinonanoate	68299-15-0	Acute Oral Toxicity Category 5; Acute Dermal Toxicity Category 5; Acute Inhalation Toxicity Category 5; Skin Effects Category 1B; Eye Effects Category 1; Chronic Aquatic Hazard Category 3	< 1
Ingredients not contributing to classification			balance

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

### Section 4 – First Aid Measures

**NZ Poisons Centre 0800 POISON (0800 764 766) | NZ Emergency Services: 111**

#### Eye contact:

Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

#### Skin or hair contact:

Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.

#### Inhalation:

If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.

#### Ingestion:

Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

#### General advice and advice for physicians:

Treat symptomatically

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 0800 764766 from anywhere in New Zealand (13 1126 in Australia) and is available at all times. Have this SDS or product label with you when you call.

### Section 5 - Fire-Fighting Measures

#### Extinguishing media:

Foam; water spray; carbon dioxide

#### Special hazards due to combustion:

High temperature decomposition products include silicon dioxide, small amounts of formaldehyde, formic acid, acetic acid and traces of silicon polymers. These gases may ignite and, depending on circumstances, may cause the resin/polymer to ignite. An outer skin of silica may also form. Extinguishing of fire, beneath the skin, may be difficult. Combustible. Will burn if ignited.

#### Advice for fire-fighters:

Alert Fire & Emergency New Zealand and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water course. Consider evacuation (or protect in place). Fight fire from a safe distance, with adequate cover. If safe, switch off electrical equipment until vapour fire hazard removed. Use water delivered as a fine spray to control the fire and cool adjacent area. Avoid spraying water onto liquid pools. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire.

**Section 6 - Accidental Release Measures****Minor Spills**

Slippery when spilt. Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety goggles. Trowel up/scrape up.

Place spilled material in clean, dry, sealed container. Flush spill area with water.

**Major Spills**

Minor hazard. Clear area of personnel. Alert Fire & Emergency New Zealand and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment as required. Prevent spillage from entering drains or water ways. Contain spill with sand, earth or vermiculite.

Collect recoverable product into labelled containers for recycling. Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal. Wash area and prevent runoff into drains or waterways. If contamination of drains or waterways occurs, advise emergency services.

**Section 7 - Handling and Storage****Handling:**

Containers, even those that have been emptied, may contain explosive vapours. Do NOT cut, drill, grind, weld or perform similar operations on or near containers. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

**Storage:**

Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

**Section 8 - Exposure Controls/Personal Protection****Exposure limits:**

CAS no.	Substance or ingredient	WES-TWA	WES-STEL
68299-15-0	Diocetyl tin dinonoate	0.1 mg/m <sup>3</sup>	0.2 mg/m <sup>3</sup>



The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

**Engineering Controls:**

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be

highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

**Exposure controls:**

Control	Protective measure
Eye	Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent] 
Respiratory	not normally required
Skin	Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. 

### Section 9 - Physical and Chemical Properties

#### General substance properties:

Property	Details
Appearance	Viscous Paste
Odour	Characteristic
pH	No data
Vapour pressure	No data
Viscosity	No data.
Boiling Point	No data
Volatile materials	No data
Freezing/melting point	No data
Solubility	Insoluble in water
Specific gravity/density	0.97 g/ml
Flash point	No data
Auto-ignition temperature	No data
Upper and lower flammability limits	Lower – %      Upper - %
Corrosiveness	No data.

### Section 10- Stability and Reactivity

#### Stability:

Stable under normal conditions.

#### Conditions to avoid:

Exposure to excessive heat, open flames and sparks. Avoid conditions that favour the formation of excessive mists and/or fumes. Contact with water may release flammable gases. Contact with water causes a chemical reaction

#### Incompatible materials to avoid:

Mild steel; Copper alloys; strong acids

#### Hazardous decomposition products:

Combustion will result in the release of carbon monoxide; carbon dioxide, silicon dioxide and other toxic vapours

### Section 11 - Toxicological Information

#### Acute toxicity:

Test	Data and symptoms of exposure
<b>Inhaled</b>	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. The major toxic effects of MEKO, regardless of the route of administration, are anaemia with breakdown of red blood cells, rapid breathing and reversible reduction in spontaneous activity, motor coordination and muscle tone. At extremely high concentrations it may cause unconsciousness and failure of breathing. Not normally a hazard due to non-volatile nature of product
<b>Oral</b>	High molecular weight material; on single acute exposure would be expected to pass through gastrointestinal tract with little change / absorption. Occasionally accumulation of the solid material within the alimentary tract may result in formation of a bezoar (concretion), producing discomfort. The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
<b>Dermal</b>	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. Skin application with methyl ethyl ketoxime under an occlusive dressing produced mild irritation with redness, swelling and wheals. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
<b>Eye</b>	This material can cause eye irritation and damage in some persons. 0.1 ml of methyl ethyl ketoxime can be corrosive to the eye. Eye exposure to silicone fluids causes temporary irritation of the conjunctiva. Injection into the specific structures of the eye, however, causes corneal scarring, permanent eye damage, allergic reactions and cataract, and may lead to blindness.
<b>Chronic</b>	Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Methyl ethyl ketoxime causes an immediate but transient central nervous system depression, dose-related decreases in red blood cell counts accompanied by a compensatory marked increase in number of immature red cells, suggesting rapid red cell breakdown. Other effects include dose-related increase in spleen, liver and kidney weights. Deposits of iron have been reported in the liver and spleen at repeated high doses. This may increase risk of liver tumours. The above are derived from results in animal testing. Amorphous silicas generally are less hazardous than crystalline silicas, but the former can be converted to the latter on heating and subsequent cooling. Inhalation of dusts containing

	crystalline silicas may lead to silicosis, a disabling lung disease that may take years to develop. Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin.
--	---

	Oral LD <sub>50</sub> mg/m <sup>3</sup>	Dermal LD <sub>50</sub> mg/m <sup>3</sup>	Inhalation LC <sub>50</sub> mg/L
Silicones and siloxanes, di-Me, hydroxy-terminated	> 5000	> 2000	> 15.3125/7h
Methyltri(methylethylketoxime)silane	> 2260	> 2000	
N-[3-(trimethoxysilyl)propyl]ethylenediamine	1897	> 2000	
Diocetyl tin dinonoate	> 2000	> 2000	

### Section 12 - Ecological Information

Very toxic to terrestrial invertebrates.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites. **Do NOT discharge to sewer or waterway**

	Fish mg/L	Crustacea mg/L	Algae mg/L
Methyltri(methylethylketoxime)silane	LC <sub>50</sub> 0.00074	EC <sub>50</sub> > 120	EC <sub>50</sub> 0.00104 NOEC 1
N-[3-(trimethoxysilyl)propyl]ethylenediamine	LC <sub>50</sub> 597	EC <sub>50</sub> 81	EC <sub>50</sub> 1 NOEC 1.6
Diocetyl tin dinonoate	LC <sub>50</sub> 5.6	EC <sub>50</sub> 0.17 NOEC 0.001 – 0.44	EC <sub>50</sub> 0.17

	Persistence H <sub>2</sub> O/ Soil	Persistence Air	Bioaccumulation	Mobility
Methyltri(methylethylketoxime)silane	HIGH	HIGH	LOW	LOW
N-[3-(trimethoxysilyl)propyl]ethylenediamine	HIGH	HIGH	LOW	LOW

### Section 13 - Disposal Considerations

Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product.

DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal.

In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible or consult manufacturer for recycling options. Consult Land Waste Authority for disposal. Bury or incinerate residue at an approved site. Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled. The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

Only dispose to the environment if a tolerable exposure limit has been set for the substance. Only deposit the hazardous substance into or onto a landfill or sewage facility or incinerator, where the hazardous substance can be handled and treated appropriately.

### Section 14 - Transport Information

NOT REGULATED

### Section 15 - Regulatory Information

HSNO approval number and Group Standard:

HSR002670

Surface Coatings & Colourants (Subsidiary Hazard)

### Group Standard conditions and other regulations:

Condition	Requirement
<b>SDS</b>	Safety data sheet must be available to a person handling the substance within 10 minutes.
<b>Emergency plan</b>	Required when present in quantities > 1000 Lt
<b>Certified handler</b>	Not required
<b>Tracking</b>	Not required
<b>Bunding and secondary containment</b>	Not required
<b>Signage</b>	Required when present in quantity > 1000 Lt
<b>Compliance certificate</b>	Not required
<b>Hazardous Atmosphere zone</b>	Not required
<b>Fire extinguisher</b>	Not required

### National Inventories

Australia	AICS	Y
Canada	DSL	Y
Canada	NDSL	N
China	IECSC	Y
Europe	EINEC/ELINCS/NLP	N
Japan	ENCS	N
Korea	KECI	Y
New Zealand	NZIoC	Y
Philippines	PICCS	Y
USA	TSCA	Y

Y = All ingredients are on the inventory

### Section 16 – Other Information

#### Date of this preparation

February 2019

Initial Preparation

#### Abbreviations:

Abbreviation	Description
CAS number	Number assigned to chemical in the Chemical Abstracts Service registry
HAZCHEM code	Code used by fire-fighters to determine correct method of action in the case of fire
HSNO	Hazardous Substances and New Organisms (Act)

ICAO Technical Instructions	International Civil Aviation Organization Technical Instructions
IMDG code	International Maritime Dangerous Goods code controlled by the International Maritime Organization (IMO)
LC <sub>50</sub>	Lethal concentration 50% - concentration fatal to 50% of the tested population
LD <sub>50</sub>	Lethal dose 50% - dose fatal to 50% of the tested population
NZS 5433	New Zealand Standard 5433 (Standard for the Transport of Dangerous Goods on Land)
SDS	Safety data sheet
STEL	Short term exposure limit
TWA	Time weighted average (typically measured as 8 hours)
UN number	United nations number
WES	Workplace exposure standard

### References

Chemical properties and HSNO classifications derived from the New Zealand chemical classification information database (CCID). [www.epa.govt.nz](http://www.epa.govt.nz).

Workplace exposure limits derived from Workplace Exposure Standards and Biological Exposure Indices 9th Edition.

***The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other material or in any process, unless specified in the text.***

This SDS was prepared by Collievale Enterprises Ltd in accord with the Hazardous Substances (Safety Data Sheets) Notice 2017  
<http://www.collievale.com> Phone +64 7 5432428

End of MSDS